Waikato Building Consent Group

Periodic Inspection of Existing Pool

	Schedule of Fencing of Swimming Pool Act 1987	
Applicant's	Consent	
Name:	No:	
Property	Pool No.:	
Address: No ITEMS TO BE CHECKED [Checked against the approved Building Consent (BC) documents]		
Key:		
Decision : $$ or P = Pass X or F = Fail, further inspection required I or $-$ or NA = Not Applicable		
Reason for decision: Compliance or non compliance with the approved		
NOTE: Portable Pools: Portable pools are treated in the same way as other residential pools. They must have barriers that restrict access by young children if they are filled or partly filled with water. Portable pools with a maximum depth of water of less than 400mm are exempt.		
SMALL HEATED POOL Not applicable (MBIE Guidance)		
Means to restrict access when pool is not in use is compliant:	Side walls of pool cannot be climbed	
Fence: Complies with <u>Schedule</u> , FSA1987 (Complete below	Signage on cover indicating its child safety features	
section for other pools)	Closed over must restrict entry of children under 5 years of	
Cover:	age when closed (latches and lockable)	
 Water surface area is 5 square metres or less Side walls of pool are 760mm or more above the 	 Withstand a foreseeable load Be readily returned to the closed position 	
adjacent floor or ground level		
OTHER RESIDENTIAL POOL Not applicable	(<u>Schedule</u> FSA1987, Building Act 2004)	
POOL AREA	□ The spacing between adjacent vertical pales, panels, or	
No vegetable garden	posts does not exceed 100 mm at any point.	
No clothes line	All non-vertical fencing supports, rails, rods, and wires, and bracing are inaccessible for climbing from the outside of	
No children's sand-pits, stand-alone slides, swings, garden sheds etc.	the pool enclosure at time of inspection.	
 No pet doors to immediate pool area 	All non-vertical fencing supports, rails, rods, and wires, and	
FENCE HEIGHT- the fence shall extend:	bracing on the outside of the fence are NO less than 900 mm apart, and the vertical boards do not exceed 10 mm	
At least 1.2 m above the ground on the outside of the fence	apart at any point. There are no other horizontal elements	
At least 1.2 m above any permanent projection or object	between these two supports, rails, rods, and wires, or	
permanently placed on the ground outside and within 1.2 m of the fence	bracings at any point. All non-vertical fencing supports, rails, rods, and wires, and bracing on the outside of the	
 Where perforated fencing material has openings greater than 	fence are NO less than 900 mm apart, and the vertical	
10mm in diameter and less than 50mm, the fence height	boards do not exceed 10 mm apart at any point. There are no other horizontal elements between these two supports,	
must be no less than 1.8 m above the ground / projection /	rails, rods, and wires, or bracings at any point.	
object. Where perforated fencing material has openings less	Perforated fencing material: openings must not be greater	
than10mm, fence height can be reduced to 1.2 m above the	than 50 mm in diameter.	
ground / projection / object.	All perforated fencing materials are firmly attached to a supporting structure or otherwise constructed to prevent	
GROUND CLEARANCE	access of children under the age of 6 years	
Any clearance between the bottom of the fence / gate and ground / permanent projection shall not exceed 100 mm	OPERATION OF GATES AND DOORS	
GATES AND DOORS	Latching device accessibility:	
Gates and doors cannot open inwards towards the	Every gate or door leading to the immediate pool area	
immediate pool area.	shall be fitted with a latching device Where the latching device is accessible from the outside of	
Gates and doors must be clear of any obstruction that could	the fence only by reaching:	
hold them open. No other means of holding the gate or door open is provided	 over the fence / gate or door, or 	
 When lifted up or pulled down a gate or door it does not 	 through a hole in the fence / gate / door; 	
release the latching device or come off its hinges or provide	the latching device and the lowest point of any hole	
a ground clearance greater than 100 mm	giving access to it, shall be at least 1.2 metres above the ground on the outside of the fence	
FENCING MATERIALS see FSP Act 1987	Height of latching device:	
All materials / components are durable and erected so as to inhibit any child less than 6 years from climbing over or	□ Where the latching device is otherwise accessible from the	
crawling under the fence from the outside.	outside of the fence / gate / door, the latching device shall be at least 1.5 m above the ground on the outside of fence	
Waikato		
DISTRICT COUNCIL DISTRICT COUNCIL DISTRICT COUNCIL DISTRICT COUNCIL DISTRICT COUNCIL DISTRICT COUNCIL		

WBCG INS-18 Periodic Pools Inspection - FOSPA Version 2024-01-26

	Pool No.:	
Self-closing:	WINDOWS IN BUILDING WALLS	
automatically return the gate / door to the closed position; and operate the latching device when the gate / door is stationary and 150 mm from the closed position	All windows within 1200 mm of the floor / permanent object are fitted with a window restrictor stay, restricting the opening to 100 mm or are fitted with a latching device at least 1500 mm from the floor / permanent object	
DOORS IN BUILDING WALLS In Not applicable Where a building forms part of a fence (and pool is not inside the building), a door in the building wall giving access to the pool area does not have to comply with clauses 8 to 10 (See section for GATES AND DOORS) if the Territorial Authority is satisfied that: Image: Compliance with these clauses is impossible, unreasonable or in breach of another Act, regulation or bylaw; and (Note: visual impact is not accepted by MBIE as a reason for non-compliance, pg 20 & 22 Guidelines to FSA for TAs) Image: The door is fitted with a lock that, when properly operated, prevents the door from being readily opened by children under the age of 6 years	ABOVE GROUND POOLS □ Not applicable No fence required if: □ Side walls of the pool are > 1.2 m above the adjacent ground level or any permanent projection from or object standing on the ground □ The outside surface of the pool's side walls is constructed so as to inhibit climbing □ Any means of access to the interior of the swimming pool can be readily removed or rendered inoperable, and is removed or rendered inoperable when the pool is not in use.	
Comments if required		
Photos attached (if relevant)		
INSPECTION OUTCOME [Tick the correct outcome: e.g. ☑ PASS or ☑		
Pool complies: PASS FAIL. Repeat inspection required Additional fee Issue Notice to Fix	REPEAT INSPECTION: Pool complies: PASS Additional fee Issue Notice to Fix Issue Infringement Notice	
Officer Name:	Officer Name:	
Signature: Date:	Signature: Date:	
HAURAKI DISTRICT COUNCIL DISTRICT COUNCI		

WBCG INS-18 Periodic Pools Inspection - FOSPA Version 2024-01-26